



Rayvenlights®



1. Feature of Rayven unframed LED Oyster ceiling light :

- Full range of size : 10"/12"/16"
- Power: 12W/18W/25W
- Sensor/Emergency/Sensor+Emergency
(12"/16")/switchablecolor(3000K/4000K/5000K/6000K)/Dimmable(when no sensor)
- IP65 (Balcony & Bathroom available)
- Quick terminal(save labor cost)
- Emergency 3 hours with integrated Emergency driver

2. Application:

Unframed LED Oyster ceiling light is widely applied to which traditional fluorescent lamps would normally be used. It Appears that needs light, such as, banks, hotels, stores, commercial buildings, shopping malls, supermarket, underground garage&etc.





Rayvenlights®

Model	RAV12OLB21	RAV18OLB31	RAV25OLB31
Wattage	12W/18W	18W/25W	25W/35W
Lumen	120LM/W135LM/W		
Beam angle	110°		
CCT Change	3000K / 4000K / 5000K		
CRI	Ra>80		
SDCM	SDCM <3		
Lifespan	50,000hrs		
Voltage	220-240VAC		
Temperature	-20°C-45°C		
Product size	Ø250*62mm	Ø300*62mm	Ø380*62mm
Dimmable option	Triac-dim, DALI dim, Tuya Smart Dim		
ERP	up to D		
Flicker free	SVM<0.4		
Dual Power	Yes		
Sensor function	Microwave Sensor, Master Slave Sensor		
IP-class	IP65		
IK-class	IK10		
Insulation Class	Class II		
Material	PC		
Environment	Indoors		
Installation	Surface mounted		
Warranty	5 years		
Approval	CE,EMC,LVD,ROHS,ERP,UKCA		

