



Rayvenlights®



K series LED Ceiling light, all the electronic part are with separated module, Driver Kit, Microwave Sensor Kit, Emergency Kit and LED PCB are easily maintain with plug & play connection.

Twin-Power, 2Color temperature changeable, up to 120lm/W, CRI>80 / CRI>90, SDCM<3 & 5 Years Warranty, IP54, IK10, with smooth & uniform lighting performance.

Functions: Microwave Sensor, Master-Slave Sensor(Wired & Wireless mode), Corridor Sensor, 3Hrs Emergency.





Rayvenlights®

Model	RAVOLK2250A	RAVOLK2300A	RAVOLK2400A
Wattage	8W/13W	17W/21W	21W/30W
Lumen	120LM/W		
Beam angle	110°		
CCT Change	3000K / 4000K		
CRI	Ra>80 Ra>90		
SDCM	SDCM <3		
Lifespan	50,000hrs		
Voltage	220-240VAC		
Temperature	-20°C-45°C		
Product size	Ø250*60mm	Ø300*60mm	Ø400*60mm
Dimmable option	Triac-dim, DALI dim		
ERP	up to D		
Flicker free	According to new ERP standard		
Dual Power	YES		
Emergency	3hrs emergency		
IP-class	IP54		
IK-class	IK10		
Insulation Class	Class II		
Material	PC		
Environment	Indoors		
Installation	Surface mounted, Suspended		
Warranty	5 years		
Approval	CE,EMC,LVD,ROHS,ERP,UKCA		

