



# Attestation of Compliance

Reference No. : LCS210811036BS

Applicant : FOSHAN RAYVEN LIGHTING CO., LTD

Address : A1 New Lighting Source Industry Zone, Luocun, Nanhai District,  
Foshan, Guangdong, China, 528200

Product : Ceiling Light

Trade Mark : Rayvenlights

Model(s) : Details refer to ANNEX I

Parameters : Details refer to ANNEX I

Tested according to : EN IEC 60598-2-1:2021; EN IEC 60598-1:2021; EN 62493:2015;  
EN IEC 62031:2020 EN 61347-1:2015+A1:2021;  
EN 61347-2-13:2014+A1:2017

The submitted products have been tested by us with the listed standards.

This Attestation of Compliance is issued according to the council Directive 2014/35/EU, Referred to as the Low Voltage Directive. It confirms that the listed product complies with all essential requirements of the LVD Directive and applies only to the sample and its technical documentation submitted to Shenzhen LCS Compliance Testing Laboratory Ltd. for testing.

After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant Directives have to be observed.



Date of issue: October 29, 2021

Manager





# ANNEX I:

Reference No. : LCS210811036BS

Model name	Rating
RAVOLD2380A	220-240V~, 50/60Hz, 28W, IP54, ta.25℃, Class II
RAVOLD2380B	220-240V~, 50/60Hz, 28W, IP54, ta.25℃, Class II
RAVOLD2380C	220-240V~, 50/60Hz, 28W, IP54, ta.25℃, Class II
RAVOLD2380D	220-240V~, 50/60Hz, 28W, IP54, ta.25℃, Class II
RAVOLD2300	220-240V~, 50/60Hz, 15W, IP54, ta.25℃, Class II
RAVOLD2300A	220-240V~, 50/60Hz, 15W, IP54, ta.25℃, Class II
RAVOLD2300B	220-240V~, 50/60Hz, 15W, IP54, ta.25℃, Class II
RAVOLD2300C	220-240V~, 50/60Hz, 15W, IP54, ta.25℃, Class II
RAVOLD2300D	220-240V~, 50/60Hz, 15W, IP54, ta.25℃, Class II
RAVOLD2250	220-240V~, 50/60Hz, 12W, IP54, ta.25℃, Class II
RAVOLD2250A	220-240V~, 50/60Hz, 12W, IP54, ta.25℃, Class II
RAVOLD2250B	220-240V~, 50/60Hz, 12W, IP54, ta.25℃, Class II
RAVOLD2250C	220-240V~, 50/60Hz, 12W, IP54, ta.25℃, Class II
RAVOLD2250D	220-240V~, 50/60Hz, 12W, IP54, ta.25℃, Class II

