



Rayvenlights®



- 1.IP65 IK10 Modular Design Bulkhead
- 2.CC Power:9W / 12W / 14W & 12W / 16W / 20W
- 3.CCT:3000K / 4000K / 5000K
- 4.Size:φ320xH80 , φ380xH80mm
- 5.Multi Function:3Hrs Emergency , Microwave Sensor , Corridor Sensor , Master Slave Sensor available
- 6.Light Control:Triac Dim , DALI Dim , 0-10V Dim
- 7.Surface Mounted & Wall Mount Suitable
- 8.Interchangeable Bezel in White / Black / Polished Chrome / Brushed Steel



0-10V





Rayvenlights®

Model	RAVOLJ3200A	RAVOLJ3800A
Wattage	9W/12W/14W	12W/16W/20W
Lumen	1200-1600lm	1600-2000lm
Beam angle	100°	
CCT Change	3000K / 4000K / 5000K	
CRI	Ra>80	
SDCM	SDCM <6	
Lifespan	50,000hrs	
Voltage	220-240VAC	
Temperature	-20°C- 40°C	
Product size	Ø320*80mm	Ø380*80mm
Dimmable option	DALI, 0-10V	
Flicker free	SVM<0.4	
Dual Power	YES	
Sensor function	Master-slave sensor, Corridor sensor	
Emergency	3hrs emergency	
IP-class	IP65	
IK-class	IK10	
Insulation Class	Class II	
Material	PC / ABS	
Environment	Balcony, Corridor	
Installation	Surface mounted	
Warranty	5 years	
Approval	CE , UKCA , SAA , ROHS , EMC , LVD , ERP	

